



- Unmanaged Fast Ethernet Switch
- 5x 10/100BaseT(X) (RJ45)
- Supports IEEE 802.3 /ab /u /x /az
- 10/100 Full/Half-Duplex, MDI/MDI-X auto-detection
- 12VDC with Jack and Terminal Block (<4W)
- Operating temperature ranges from -5° ~ +45°C
- IP40, Metal housing
- DIN-Rail and Wall Mounting

NETLANCE ES-P05F2-MU

Fast Ethernet Switch



ETHERNET

Connector	RJ45
Ports	5
Transmission Rate	10/100 Mbps
Standards	IEEE 802.3 /u /x /az
Auto MDI/MDI-X	Yes
MAC Address Table	2K

POWER

Input Voltage	12 VDC
Input Current	0.5A
Power Consumption	<4 W Max
Connector	2-pin Terminal Block and Jack
Reverse Polarity Protection	No
Redundancy	No

PHYSICAL CHARACTERISTICS

Housing	IP40 protection, Metal housing
Dimension (W x H x D)	100mm x 77mm x 31mm
Weight	0.35Kg
Installation	DIN-Rail and Wall Mount
Reset Button	No
Warranty	1 year

ENVIRONMENTAL LIMITS

Operating Temperature	-5°C ~ +45°C (23° ~ 113°F)
Storage Temperature	-10°C ~ +70°C (14° ~ 158°F)
Ambient Relative Humidity	5 ~ 90%RH (Non-condensing)

*All product information may subject to change without prior notice.

*The rights of all brand names, product names and trademarks belong to their respective owners.

SARC ITALIA SRL

Strada Albareto, 503 - 41122 Modena - ITALY
Tel. +39 059 8751076 Fax. +39 059 8751025

Website: www.indatech.it

Email: info@indatech.it

Copyright © 2024 INDATECH. All rights reserved.