



- Unmanaged Gigabit Ethernet Switch
- 5x 10/100/1000BaseT(X) (RJ45)
- Supports IEEE 802.3 /ab /u /x /az
- 10/100/1000 Full/Half-Duplex, MDI/MDI-X auto-detection
- 12VDC with Jack and Terminal Block (<4W)
- Operating temperature ranges from -5° ~ +45°C
- IP40, Metal housing
- DIN-Rail and Wall Mounting

NETLANCE ES-P05G2-MU

Gigabit Ethernet Switch



ETHERNET

| | |
|-------------------|--------------------------|
| Connector | RJ45 |
| Ports | 5 |
| Transmission Rate | 10/100/1000 Mbps |
| Standards | IEEE 802.3 /ab /u /x /az |
| Auto MDI/MDI-X | Yes |
| MAC Address Table | 2K |

POWER

| | |
|-----------------------------|-------------------------------|
| Input Voltage | 12 VDC |
| Input Current | 0.5A |
| Power Consumption | <4 W Max |
| Connector | 2-pin Terminal Block and Jack |
| Reverse Polarity Protection | No |
| Redundancy | No |

PHYSICAL CHARACTERISTICS

| | |
|-----------------------|--------------------------------|
| Housing | IP40 protection, Metal housing |
| Dimension (W x H x D) | 100mm x 77mm x 31mm |
| Weight | 0.35Kg |
| Installation | DIN-Rail and Wall Mount |
| Reset Button | No |
| Warranty | 1 year |

ENVIRONMENTAL LIMITS

| | |
|---------------------------|-------------------------------|
| Operating Temperature | -5°C ~ +45°C (23° ~ 113°F) |
| Storage Temperature | -10°C ~ +70°C (14° ~ 158°F) |
| Ambient Relative Humidity | 5 ~ 90%RH (Non-condensing) |

*All product information may subject to change without prior notice.

*The rights of all brand names, product names and trademarks belong to their respective owners.

SARC ITALIA SRL

Strada Albareto, 503 - 41122 Modena - ITALY
Tel. +39 059 8751076 Fax. +39 059 8751025

Website: www.indatech.it

Email: info@indatech.it

Copyright © 2024 INDATECH. All rights reserved.